

# PRODUCT BRIEF

Smooth Concrete

Pre-cast, lightweight concrete panels imposed with a smooth texture applied to walls, fireplaces and more. Suitable for non-combustible interior and exterior applications.

## Recommended Sizes

Available in 5/8" (16mm) thickness in the following dimensions:

24" x 36" (609.6mm x 914.4mm)

30" x 30" (762mm x 762mm)

24" x 72" (609.6mm x 1828.8mm)

30" x 48" (762mm x 1219.2mm)

16" x 48" (406.4mm x 1219.2mm)

*Made to order. Custom sizes available*

## Weight

24" x 36" Panel: 19.7kg (43.30 lbs)

30" x 30" Panel: 20.5kg (45.10 lbs)

24" x 72" Panel: 39.4kg (86.59 lbs)

30" x 48" Panel: 32.8kg (72.16 lbs)

16" x 48" Panel: 17.5kg (38.49 lbs)

## Joint Options

Best suited to be installed with butt joints.

## Prepared Substrate

The substrate should be smooth, plumb, level and stable prior to installation.

## Adhesive



We recommend an instant grab MS Polymer adhesive such as Xcel IGA for both interior and exterior use.

## Caulking

Colour matched and sanded. We recommend using MAPEI Keracaulk or TEC Accucolour.

## Sealer

Concrete is a porous material, and most of our concrete products are sealed before shipping or installation unless discussed with the client. We use various sealers based on the concrete applicati



Butt Joint

